


Product Type: Drywall Track
Product Definition: 250T125-33 33ksi
CSI Code: 09.22.16.13



Profile Properties:

Web Depth	2,500 in	Yield Strength:	33 ksi
Flange Width	1,250 in	Unit Weight	0,57 lb/ft
Design Thickness	0,0346 in	Finish	G40
Minimum Thickness	0,0329 in	Color Coding	White

Gross Section Properties:

Cross Sectional Area	Agross	0,1720 in ²
Moment of Inertia, x-axis	Ix	0,1685 in ⁴
Radius of Gyration, x-axis	rx	1,0020 in
Moment of Inertia, y-axis	Iy	0,0267 in ⁴
Radius of Gyration, y-axis	ry	0,3989 in

Torsional Properties:

St. Venant Torsion Constant	J x 1000	0,0670 in ⁴
Warping Constant	Cw	0,0263 in ⁶
Distance Between Shear Axis and Neutral Axis	x0	-0,7676 in
Polar Radius of Gyration	r0	1,3238 in
Torsional Flexural Constant	β	0,6638
Limit of Unbraced Length	Lu	35,42 in





Effective Section Properties:

Effective Area	A _{eff}	0,1509 in ²
Effective Moment of Inertia for Deflection	I _{xe}	0,1560 in ⁴
Effective Section Modulus	S _{xe}	0,1026 in ³
Allowable Bending Moment	M _a	1,9600 in.K
Allowable Shear Force	V _{ag}	987 lbs

Codes & Standards:

- Calculations are based on AISI S220-20 and AISI S100-16.
- Complies with IBC2021, ASTM C645, ASTM C754, ASTM A653, ASTM A1003, ASTM E72
- Intertek Certificate of Compliance No: COC-WHI23-37729201
- LEED / Sustainability Credits: Environmental Product Declaration S-P Code: S-P-00869

