
PRODUCT SUBMITTAL SHEET

Product Type: Structural Stud

Product Definition: 362S250-68-P (50ksi, Punched)

CSI Code: 05 41 00



Profile Properties:

Web Depth	3.625 in	Yield Strength Fy:	50 ksi
Flange Width	2.500 in	Unit Weight	2.27 lb/ft
Stiffening Lip	0.6250 in	Punchout Width / Length	1-1/2'' – 4''
Design Thickness	0.0713 in	Coating	G60 or G90
Thickness	68 mils (14 Ga)	Min. Steel Thickness	0.0677 in
Inside Bend Radius	0.1069 in	Tensile Strength Fu	65 ksi

Gross Section Properties:

Cross Sectional Area	Agross	0.6663 in2
Member weight per foot of length		2.27 lb/ft
Moment of Inertia. x-axis	Ix	1.4908 in4
Section Modulus. x-axis	Sx	0.8225 in3
Radius of Gyration. x-axis	rx	1.4958 in
Moment of Inertia. y-axis	Iy	0.5777 in4
Radius of Gyration. y-axis	ry	0.9311 in

Torsional Properties:

St. Venant Torsion Constant	J x 1000	1.1291 in4
Warping Constant	Cw	1.8373 in6
Distance Between Shear Axis and Neutral Axis	x0	-2.1652 in
Shear Center to Web Centerline	m	1.2595 in
Polar Radius of Gyration	r0	2.7915 in
Torsional Flexural Constant	β	0.3984
Limit of Unbraced Length	Lu	44.08 in

Effective Section Properties:

Effective Area	Aeff	0.5264 in2
Effective Moment of Inertia for Deflection	Ixe	1.3741 in4
Effective Section Modulus	Sxe	0.7143 in3
Allowable Bending Moment	Ma	21.3874 in.k
Allowable Moment (Distortional Buckling)	Mad	22.1727 in.k
Allowable Shear Force (Solid Section)	Vag	4370 lbs
Allowable Shear Force (Perforated Section)	VaPO	1004 lbs

Codes & Standards:

- Calculations are based on AISI S240-20 and AISI S100-16 (2020) w/S2-20.
- AISI S240-20 North American Standard for Cold-Formed Steel Structural Framing: Section A3 Material (ASTM A1003/A1003M); Section A4 Corrosion Protection (ASTM A653/A653M); Section A5 Products – thickness, shapes, tolerances, identification; Section C Installation (ASTM C1007).
- IBC 2024 International Building Code. ASTM C955. ASTM A1003. ASTM A653 SS Grade 50 Class 1. Coating G60 or G90 per AISI S240 Section A4.
- ICC-ES ESR-5905 UMS Joists, UMS Studs and UMS Tracks.
- LEED / Sustainability Credits: Environmental Product Declaration S-P Code: S-P-00869
- Note: Punch-outs 1-1/2'' × 4'' at 24'' o.c., first punch-out min. 12'' from end. Properties are for the full section away from punch-outs; VaPO accounts for the punch-out.

Structural Studs. The technical content of this literature is effective 10/30/2026 and supersedes all previous information.