
PRODUCT SUBMITTAL SHEET

Product Type: Structural Stud

Product Definition: 550S162-43-U (33ksi, Unpunched)

CSI Code: 05 41 00



Profile Properties:

Web Depth	5.500 in	Yield Strength Fy:	33 ksi
Flange Width	1.625 in	Unit Weight	1.44 lb/ft
Stiffening Lip	0.5000 in	Punchout Width / Length	None (unpunched)
Design Thickness	0.0451 in	Coating	G60 or G90
Thickness	43 mils (18 Ga)	Min. Steel Thickness	0.0428 in
Inside Bend Radius	0.0712 in	Tensile Strength Fu	45 ksi

Gross Section Properties:

Cross Sectional Area	Agross	0.4243 in2
Member weight per foot of length		1.44 lb/ft
Moment of Inertia. x-axis	Ix	1.8835 in4
Section Modulus. x-axis	Sx	0.6849 in3
Radius of Gyration. x-axis	rx	2.1069 in
Moment of Inertia. y-axis	Iy	0.1448 in4
Radius of Gyration. y-axis	ry	0.5841 in

Torsional Properties:

St. Venant Torsion Constant	J x 1000	0.2877 in4
Warping Constant	Cw	0.9054 in6
Distance Between Shear Axis and Neutral Axis	x0	-1.1029 in
Shear Center to Web Centerline	m	0.6907 in
Polar Radius of Gyration	r0	2.4487 in
Torsional Flexural Constant	β	0.7972
Limit of Unbraced Length	Lu	43.29 in

Effective Section Properties:

Effective Area	Aeff	0.2900 in2
Effective Moment of Inertia for Deflection	Ixe	1.8829 in4
Effective Section Modulus	Sxe	0.6847 in3
Allowable Bending Moment	Ma	13.5305 in.k
Allowable Moment (Distortional Buckling)	Mad	12.3110 in.k
Allowable Shear Force (Solid Section)	Vag	1550 lbs

Codes & Standards:

- Calculations are based on AISI S240-20 and AISI S100-16 (2020) w/S2-20.
- AISI S240-20 North American Standard for Cold-Formed Steel Structural Framing: Section A3 Material (ASTM A1003/A1003M); Section A4 Corrosion Protection (ASTM A653/A653M); Section A5 Products – thickness, shapes, tolerances, identification; Section C Installation (ASTM C1007).
- IBC 2024 International Building Code. ASTM C955. ASTM A1003. ASTM A653 SS Grade 33. Coating G60 or G90 per AISI S240 Section A4.
- ICC-ES ESR-5905 UMS Joists, UMS Studs and UMS Tracks.
- LEED / Sustainability Credits: Environmental Product Declaration S-P Code: S-P-00869
- Note: Supplied without web punch-outs.

Structural Studs. The technical content of this literature is effective 10/30/2026 and supersedes all previous information.