
PRODUCT SUBMITTAL SHEET

Product Type: Structural Stud

Product Definition: 1000S200-43-U (33ksi, Unpunched)

CSI Code: 05 41 00



Profile Properties:

Web Depth	10.000 in	Yield Strength Fy:	33 ksi
Flange Width	2.000 in	Unit Weight	2.29 lb/ft
Stiffening Lip	0.6250 in	Punchout Width / Length	None (unpunched)
Design Thickness	0.0451 in	Coating	G60 or G90
Thickness	43 mils (18 Ga)	Min. Steel Thickness	0.0428 in
Inside Bend Radius	0.0712 in	Tensile Strength Fu	45 ksi

Gross Section Properties:

Cross Sectional Area	Agross	0.6724 in2
Member weight per foot of length		2.29 lb/ft
Moment of Inertia. x-axis	Ix	9.0881 in4
Section Modulus. x-axis	Sx	1.8176 in3
Radius of Gyration. x-axis	rx	3.6765 in
Moment of Inertia. y-axis	Iy	0.3086 in4
Radius of Gyration. y-axis	ry	0.6775 in

Torsional Properties:

St. Venant Torsion Constant	J x 1000	0.4559 in4
Warping Constant	Cw	6.2362 in6
Distance Between Shear Axis and Neutral Axis	x0	-1.1472 in
Shear Center to Web Centerline	m	0.7435 in
Polar Radius of Gyration	r0	3.9104 in
Torsional Flexural Constant	β	0.9139
Limit of Unbraced Length	Lu	47.47 in

Effective Section Properties:

Effective Area	Aeff	0.3314 in2
Effective Moment of Inertia for Deflection	Ixe	8.1376 in4
Effective Section Modulus	Sxe	1.4702 in3
Allowable Bending Moment	Ma	29.0515 in.k
Allowable Moment (Distortional Buckling)	Mad	26.1546 in.k
Allowable Shear Force (Solid Section)	Vag	836 lbs

Codes & Standards:

- Calculations are based on AISI S240-20 and AISI S100-16 (2020) w/S2-20.
- AISI S240-20 North American Standard for Cold-Formed Steel Structural Framing: Section A3 Material (ASTM A1003/A1003M); Section A4 Corrosion Protection (ASTM A653/A653M); Section A5 Products – thickness, shapes, tolerances, identification; Section C Installation (ASTM C1007).
- IBC 2024 International Building Code. ASTM C955. ASTM A1003. ASTM A653 SS Grade 33. Coating G60 or G90 per AISI S240 Section A4.
- ICC-ES ESR-5905 UMS Joists, UMS Studs and UMS Tracks.
- LEED / Sustainability Credits: Environmental Product Declaration S-P Code: S-P-00869
- Note: Supplied without web punch-outs; holes or punch-outs in the web are outside the scope of ESR-5905 for members with h/t > 200. Web h/t exceeds 200: bearing stiffeners are required at all supports and concentrated loads per AISI S100-16 w/S2-20 Section B4 and Table B4.1-1.

Structural Studs. The technical content of this literature is effective 10/30/2026 and supersedes all previous information.