
PRODUCT SUBMITTAL SHEET

Product Type: Structural Stud

Product Definition: 250S162-54-U (50ksi, Unpunched)

CSI Code: 05 41 00



Profile Properties:

Web Depth	2.500 in	Yield Strength Fy:	50 ksi
Flange Width	1.625 in	Unit Weight	1.22 lb/ft
Stiffening Lip	0.5000 in	Punchout Width / Length	None (unpunched)
Design Thickness	0.0566 in	Coating	G60 or G90
Thickness	54 mils (16 Ga)	Min. Steel Thickness	0.0538 in
Inside Bend Radius	0.0849 in	Tensile Strength Fu	65 ksi

Gross Section Properties:

Cross Sectional Area	Agross	0.3582 in2
Member weight per foot of length		1.22 lb/ft
Moment of Inertia. x-axis	Ix	0.3698 in4
Section Modulus. x-axis	Sx	0.2959 in3
Radius of Gyration. x-axis	rx	1.0160 in
Moment of Inertia. y-axis	Iy	0.1348 in4
Radius of Gyration. y-axis	ry	0.6135 in

Torsional Properties:

St. Venant Torsion Constant	J x 1000	0.3825 in4
Warping Constant	Cw	0.2229 in6
Distance Between Shear Axis and Neutral Axis	x0	-1.4429 in
Shear Center to Web Centerline	m	0.8446 in
Polar Radius of Gyration	r0	1.8684 in
Torsional Flexural Constant	β	0.4035
Limit of Unbraced Length	Lu	33.07 in

Effective Section Properties:

Effective Area	Aeff	0.3280 in2
Effective Moment of Inertia for Deflection	Ixe	0.3649 in4
Effective Section Modulus	Sxe	0.2881 in3
Allowable Bending Moment	Ma	8.6264 in.k
Allowable Moment (Distortional Buckling)	Mad	8.7909 in.k
Allowable Shear Force (Solid Section)	Vag	2353 lbs

Codes & Standards:

- Calculations are based on AISI S240-20 and AISI S100-16 (2020) w/S2-20.
- AISI S240-20 North American Standard for Cold-Formed Steel Structural Framing: Section A3 Material (ASTM A1003/A1003M); Section A4 Corrosion Protection (ASTM A653/A653M); Section A5 Products – thickness, shapes, tolerances, identification; Section C Installation (ASTM C1007).
- IBC 2024 International Building Code. ASTM C955. ASTM A1003. ASTM A653 SS Grade 50 Class 1. Coating G60 or G90 per AISI S240 Section A4.
- ICC-ES ESR-5905 UMS Joists, UMS Studs and UMS Tracks.
- LEED / Sustainability Credits: Environmental Product Declaration S-P Code: S-P-00869
- Note: Supplied without web punch-outs.

Structural Studs. The technical content of this literature is effective 10/30/2026 and supersedes all previous information.