
PRODUCT SUBMITTAL SHEET

Product Type: Structural Stud

Product Definition: 1200S200-54-U (50ksi, Unpunched)

CSI Code: 05 41 00



Profile Properties:

Web Depth	12.000 in	Yield Strength Fy:	50 ksi
Flange Width	2.000 in	Unit Weight	3.24 lb/ft
Stiffening Lip	0.6250 in	Punchout Width / Length	None (unpunched)
Design Thickness	0.0566 in	Coating	G60 or G90
Thickness	54 mils (16 Ga)	Min. Steel Thickness	0.0538 in
Inside Bend Radius	0.0849 in	Tensile Strength Fu	65 ksi

Gross Section Properties:

Cross Sectional Area	Agross	0.9525 in2
Member weight per foot of length		3.24 lb/ft
Moment of Inertia. x-axis	Ix	17.6683 in4
Section Modulus. x-axis	Sx	2.9447 in3
Radius of Gyration. x-axis	rx	4.3068 in
Moment of Inertia. y-axis	Iy	0.3935 in4
Radius of Gyration. y-axis	ry	0.6428 in

Torsional Properties:

St. Venant Torsion Constant	J x 1000	1.0172 in4
Warping Constant	Cw	11.5501 in6
Distance Between Shear Axis and Neutral Axis	x0	-1.0316 in
Shear Center to Web Centerline	m	0.6806 in
Polar Radius of Gyration	r0	4.4750 in
Torsional Flexural Constant	β	0.9469
Limit of Unbraced Length	Lu	33.36 in

Effective Section Properties:

Effective Area	Aeff	0.3848 in2
Effective Moment of Inertia for Deflection	Ixe	14.4925 in4
Effective Section Modulus	Sxe	2.0731 in3
Allowable Bending Moment	Ma	62.0700 in.k
Allowable Moment (Distortional Buckling)	Mad	54.7555 in.k
Allowable Shear Force (Solid Section)	Vag	1377 lbs

Codes & Standards:

- Calculations are based on AISI S240-20 and AISI S100-16 (2020) w/S2-20.
- AISI S240-20 North American Standard for Cold-Formed Steel Structural Framing: Section A3 Material (ASTM A1003/A1003M); Section A4 Corrosion Protection (ASTM A653/A653M); Section A5 Products – thickness, shapes, tolerances, identification; Section C Installation (ASTM C1007).
- IBC 2024 International Building Code. ASTM C955. ASTM A1003. ASTM A653 SS Grade 50 Class 1. Coating G60 or G90 per AISI S240 Section A4.
- ICC-ES ESR-5905 UMS Joists, UMS Studs and UMS Tracks.
- LEED / Sustainability Credits: Environmental Product Declaration S-P Code: S-P-00869
- Note: Supplied without web punch-outs; holes or punch-outs in the web are outside the scope of ESR-5905 for members with h/t > 200. Web h/t exceeds 200: bearing stiffeners are required at all supports and concentrated loads per AISI S100-16 w/S2-20 Section B4 and Table B4.1-1.

Structural Studs. The technical content of this literature is effective 10/30/2026 and supersedes all previous information.