
PRODUCT SUBMITTAL SHEET

Product Type: Structural Stud

Product Definition: 550S162-33-P (33ksi, Punched)

CSI Code: 05 41 00



Profile Properties:

Web Depth	5.500 in	Yield Strength Fy:	33 ksi
Flange Width	1.625 in	Unit Weight	1.11 lb/ft
Stiffening Lip	0.5000 in	Punchout Width / Length	1-1/2'' – 4''
Design Thickness	0.0346 in	Coating	G60 or G90
Thickness	33 mils (20 Ga)	Min. Steel Thickness	0.0329 in
Inside Bend Radius	0.0764 in	Tensile Strength Fu	45 ksi

Gross Section Properties:

Cross Sectional Area	Agross	0.3270 in2
Member weight per foot of length		1.11 lb/ft
Moment of Inertia. x-axis	Ix	1.4589 in4
Section Modulus. x-axis	Sx	0.5305 in3
Radius of Gyration. x-axis	rx	2.1122 in
Moment of Inertia. y-axis	Iy	0.1134 in4
Radius of Gyration. y-axis	ry	0.5888 in

Torsional Properties:

St. Venant Torsion Constant	J x 1000	0.1305 in4
Warping Constant	Cw	0.7125 in6
Distance Between Shear Axis and Neutral Axis	x0	-1.1137 in
Shear Center to Web Centerline	m	0.6972 in
Polar Radius of Gyration	r0	2.4594 in
Torsional Flexural Constant	β	0.7949
Limit of Unbraced Length	Lu	42.20 in

Effective Section Properties:

Effective Area	Aeff	0.1978 in2
Effective Moment of Inertia for Deflection	Ixe	1.4259 in4
Effective Section Modulus	Sxe	0.5116 in3
Allowable Bending Moment	Ma	10.1102 in.k
Allowable Moment (Distortional Buckling)	Mad	8.6289 in.k
Allowable Shear Force (Solid Section)	Vag	698 lbs
Allowable Shear Force (Perforated Section)	VaPO	698 lbs

Codes & Standards:

- Calculations are based on AISI S240-20 and AISI S100-16 (2020) w/S2-20.
- AISI S240-20 North American Standard for Cold-Formed Steel Structural Framing: Section A3 Material (ASTM A1003/A1003M); Section A4 Corrosion Protection (ASTM A653/A653M); Section A5 Products – thickness, shapes, tolerances, identification; Section C Installation (ASTM C1007).
- IBC 2024 International Building Code. ASTM C955. ASTM A1003. ASTM A653 SS Grade 33. Coating G60 or G90 per AISI S240 Section A4.
- ICC-ES ESR-5905 UMS Joists, UMS Studs and UMS Tracks.
- LEED / Sustainability Credits: Environmental Product Declaration S-P Code: S-P-00869
- Note: Punch-outs 1-1/2'' × 4'' at 24'' o.c., first punch-out min. 12'' from end. Properties are for the full section away from punch-outs; VaPO accounts for the punch-out.

Structural Studs. The technical content of this literature is effective 10/30/2026 and supersedes all previous information.