
PRODUCT SUBMITTAL SHEET

Product Type: Structural Stud

Product Definition: 400S162-33-P (50ksi, Punched)

CSI Code: 05 41 00



Profile Properties:

Web Depth	4.000 in	Yield Strength Fy:	50 ksi
Flange Width	1.625 in	Unit Weight	0.94 lb/ft
Stiffening Lip	0.5000 in	Punchout Width / Length	1-1/2'' – 4''
Design Thickness	0.0346 in	Coating	G60 or G90
Thickness	33 mils (20 Ga)	Min. Steel Thickness	0.0329 in
Inside Bend Radius	0.0764 in	Tensile Strength Fu	65 ksi

Gross Section Properties:

Cross Sectional Area	Agross	0.2751 in2
Member weight per foot of length		0.94 lb/ft
Moment of Inertia. x-axis	Ix	0.6923 in4
Section Modulus. x-axis	Sx	0.3461 in3
Radius of Gyration. x-axis	rx	1.5863 in
Moment of Inertia. y-axis	Iy	0.1027 in4
Radius of Gyration. y-axis	ry	0.6109 in

Torsional Properties:

St. Venant Torsion Constant	J x 1000	0.1098 in4
Warping Constant	Cw	0.3628 in6
Distance Between Shear Axis and Neutral Axis	x0	-1.2633 in
Shear Center to Web Centerline	m	0.7682 in
Polar Radius of Gyration	r0	2.1179 in
Torsional Flexural Constant	β	0.6442
Limit of Unbraced Length	Lu	32.42 in

Effective Section Properties:

Effective Area	Aeff	0.1668 in2
Effective Moment of Inertia for Deflection	Ixe	0.6420 in4
Effective Section Modulus	Sxe	0.3064 in3
Allowable Bending Moment	Ma	9.1740 in.k
Allowable Moment (Distortional Buckling)	Mad	7.9754 in.k
Allowable Shear Force (Solid Section)	Vag	976 lbs
Allowable Shear Force (Perforated Section)	VaPO	595 lbs

Codes & Standards:

- Calculations are based on AISI S240-20 and AISI S100-16 (2020) w/S2-20.
- AISI S240-20 North American Standard for Cold-Formed Steel Structural Framing: Section A3 Material (ASTM A1003/A1003M); Section A4 Corrosion Protection (ASTM A653/A653M); Section A5 Products – thickness, shapes, tolerances, identification; Section C Installation (ASTM C1007).
- IBC 2024 International Building Code. ASTM C955. ASTM A1003. ASTM A653 SS Grade 50 Class 1. Coating G60 or G90 per AISI S240 Section A4.
- ICC-ES ESR-5905 UMS Joists, UMS Studs and UMS Tracks.
- LEED / Sustainability Credits: Environmental Product Declaration S-P Code: S-P-00869
- Note: Punch-outs 1-1/2'' × 4'' at 24'' o.c., first punch-out min. 12'' from end. Properties are for the full section away from punch-outs; VaPO accounts for the punch-out.

Structural Studs. The technical content of this literature is effective 10/30/2026 and supersedes all previous information.