
PRODUCT SUBMITTAL SHEET

Product Type: Structural Stud

Product Definition: 550S200-68-U (33ksi, Unpunched)

CSI Code: 05 41 00



Profile Properties:

Web Depth	5.500 in	Yield Strength Fy:	33 ksi
Flange Width	2.000 in	Unit Weight	2.48 lb/ft
Stiffening Lip	0.6250 in	Punchout Width / Length	None (unpunched)
Design Thickness	0.0713 in	Coating	G60 or G90
Thickness	68 mils (14 Ga)	Min. Steel Thickness	0.0677 in
Inside Bend Radius	0.1069 in	Tensile Strength Fu	45 ksi

Gross Section Properties:

Cross Sectional Area	Agross	0.7287 in2
Member weight per foot of length		2.48 lb/ft
Moment of Inertia. x-axis	Ix	3.3413 in4
Section Modulus. x-axis	Sx	1.2150 in3
Radius of Gyration. x-axis	rx	2.1414 in
Moment of Inertia. y-axis	Iy	0.3892 in4
Radius of Gyration. y-axis	ry	0.7308 in

Torsional Properties:

St. Venant Torsion Constant	J x 1000	1.2348 in4
Warping Constant	Cw	2.5308 in6
Distance Between Shear Axis and Neutral Axis	x0	-1.4649 in
Shear Center to Web Centerline	m	0.9015 in
Polar Radius of Gyration	r0	2.6954 in
Torsional Flexural Constant	β	0.7047
Limit of Unbraced Length	Lu	53.37 in

Effective Section Properties:

Effective Area	Aeff	0.6009 in2
Effective Moment of Inertia for Deflection	Ixe	3.3403 in4
Effective Section Modulus	Sxe	1.2147 in3
Allowable Bending Moment	Ma	24.0038 in.k
Allowable Moment (Distortional Buckling)	Mad	24.0095 in.k
Allowable Shear Force (Solid Section)	Vag	4348 lbs

Codes & Standards:

- Calculations are based on AISI S240-20 and AISI S100-16 (2020) w/S2-20.
- AISI S240-20 North American Standard for Cold-Formed Steel Structural Framing: Section A3 Material (ASTM A1003/A1003M); Section A4 Corrosion Protection (ASTM A653/A653M); Section A5 Products – thickness, shapes, tolerances, identification; Section C Installation (ASTM C1007).
- IBC 2024 International Building Code. ASTM C955. ASTM A1003. ASTM A653 SS Grade 33. Coating G60 or G90 per AISI S240 Section A4.
- ICC-ES ESR-5905 UMS Joists, UMS Studs and UMS Tracks.
- LEED / Sustainability Credits: Environmental Product Declaration S-P Code: S-P-00869
- Note: Supplied without web punch-outs.

Structural Studs. The technical content of this literature is effective 10/30/2026 and supersedes all previous information.