
PRODUCT SUBMITTAL SHEET

Product Type: Structural Stud

Product Definition: 800S162-43-P (33ksi, Punched)

CSI Code: 05 41 00



Profile Properties:

Web Depth	8.000 in	Yield Strength Fy:	33 ksi
Flange Width	1.625 in	Unit Weight	1.83 lb/ft
Stiffening Lip	0.5000 in	Punchout Width / Length	1-1/2'' – 4''
Design Thickness	0.0451 in	Coating	G60 or G90
Thickness	43 mils (18 Ga)	Min. Steel Thickness	0.0428 in
Inside Bend Radius	0.0712 in	Tensile Strength Fu	45 ksi

Gross Section Properties:

Cross Sectional Area	Agross	0.5371 in2
Member weight per foot of length		1.83 lb/ft
Moment of Inertia. x-axis	Ix	4.6349 in4
Section Modulus. x-axis	Sx	1.1587 in3
Radius of Gyration. x-axis	rx	2.9376 in
Moment of Inertia. y-axis	Iy	0.1599 in4
Radius of Gyration. y-axis	ry	0.5456 in

Torsional Properties:

St. Venant Torsion Constant	J x 1000	0.3641 in4
Warping Constant	Cw	2.0758 in6
Distance Between Shear Axis and Neutral Axis	x0	-0.9262 in
Shear Center to Web Centerline	m	0.6006 in
Polar Radius of Gyration	r0	3.1281 in
Torsional Flexural Constant	β	0.9123
Limit of Unbraced Length	Lu	40.15 in

Effective Section Properties:

Effective Area	Aeff	0.2940 in2
Effective Moment of Inertia for Deflection	Ixe	4.3519 in4
Effective Section Modulus	Sxe	1.0193 in3
Allowable Bending Moment	Ma	20.1409 in.k
Allowable Moment (Distortional Buckling)	Mad	18.3340 in.k
Allowable Shear Force (Solid Section)	Vag	1051 lbs
Allowable Shear Force (Perforated Section)	VaPO	1051 lbs

Codes & Standards:

- Calculations are based on AISI S240-20 and AISI S100-16 (2020) w/S2-20.
- AISI S240-20 North American Standard for Cold-Formed Steel Structural Framing: Section A3 Material (ASTM A1003/A1003M); Section A4 Corrosion Protection (ASTM A653/A653M); Section A5 Products – thickness, shapes, tolerances, identification; Section C Installation (ASTM C1007).
- IBC 2024 International Building Code. ASTM C955. ASTM A1003. ASTM A653 SS Grade 33. Coating G60 or G90 per AISI S240 Section A4.
- ICC-ES ESR-5905 UMS Joists, UMS Studs and UMS Tracks.
- LEED / Sustainability Credits: Environmental Product Declaration S-P Code: S-P-00869
- Note: Punch-outs 1-1/2'' × 4'' at 24'' o.c., first punch-out min. 12'' from end. Properties are for the full section away from punch-outs; VaPO accounts for the punch-out.

Structural Studs. The technical content of this literature is effective 10/30/2026 and supersedes all previous information.