PRODUCT SUBMITTAL SHEET

Product Type: Structural Track

Product Definition: 1200T125-54 (50ksi)

CSI Code: 05 41 00



Profile Properties:

Web Depth (inside)	12.000 in	Yield Strength Fy:	50 ksi
Flange Width	1.250 in	Unit Weight	2.77 lb/ft
Web Depth (outside)	12.1132 in	Punchout Width / Length	None
Design Thickness	0.0566 in	Coating	G60 or G90
Thickness	54 mils (16 Ga)	Min. Steel Thickness	0.0538 in
Inside Bend Radius	0.0849 in	Tensile Strength Fu	65 ksi

Gross Section Properties:

Cross Sectional Area	Agross	0.8152 in2
Member weight per foot of length		2.77 lb/ft
Moment of Inertia. x-axis	Ix	13.0972 in4
Section Modulus. x-axis	Sx	2.1625 in3
Radius of Gyration. x-axis	rx	4.0083 in
Moment of Inertia. y-axis	Iy	0.0600 in4
Radius of Gyration. y-axis	ry	0.2714 in

Torsional Properties:

St. Venant Torsion Constant	J x 1000	0.8705 in4
Warping Constant	Cw	1.7913 in6
Distance Between Shear Axis and Neutral Axis	x0	-0.3347 in
Shear Center to Web Centerline	m	0.2310 in
Polar Radius of Gyration	r0	4.0314 in
Torsional Flexural Constant	β	0.9931
Limit of Unbraced Length	Lu	13.02 in

Effective Section Properties:

Effective Area	Aeff	0.2414 in2
Effective Moment of Inertia for Deflection	Ixe	9.4450 in4
Effective Section Modulus	Sxe	1.2766 in3
Allowable Bending Moment	Ma	38.2222 in.k
Allowable Shear Force	Vag	1364 lbs

Codes & Standards:

- Calculations are based on AISI S240-20 and AISI S100-16 (2020) w/S2-20.
- AISI S240-20 North American Standard for Cold-Formed Steel Structural Framing: Section A3 Material (ASTM A1003/A1003M); Section A4 Corrosion Protection (ASTM A653/A653M); Section A5 Products – thickness, shapes, tolerances, identification; Section C Installation (ASTM C1007).
- IBC 2024 International Building Code. ASTM C955. ASTM A1003. ASTM A653 SS Grade 50 Class 1. Coating G60 or G90 per AISI S240 Section A4.
- ICC-ES ESR-5905 UMS Joists, UMS Studs and UMS Tracks.
- LEED / Sustainability Credits: Environmental Product Declaration S-P Code: S-P-00869
- Note: Tracks are manufactured without web punch-outs. Web depth designation is the inside-to-inside dimension; outside web depth = designation + 2 × design thickness (tolerance 0 to +1/8''). Web h/t exceeds 200: bearing stiffeners are required at all supports and concentrated loads per AISI S100-16 w/S2-20 Section B4 and Table B4.1-1.

Structural Track. The technical content of this literature is effective 10/30/2026 and supersedes all previous information.