


Product Type: Structural Track

Product Definition: 362T125-54 (50ksi)

CSI Code: 05 41 00



Profile Properties:

Web Depth	3.620 in	Yield Strength F_y :	50 ksi
Flange Width	1.250 in	Unit Weight	1.18 lb/ft
Design Thickness	0.0566 in	Coating	G60
Thickness	54mils (16Ga)		

Gross Section Properties:

Cross Sectional Area	A_{gross}	0.3457 in ²
Member weight per foot of length		1.18 lb/ft
Moment of Inertia. x-axis	I_x	0.7205 in ⁴
Radius of Gyration. x-axis	r_x	1.4437 in
Moment of Inertia. y-axis	I_y	0.0481 in ⁴
Radius of Gyration. y-axis	r_y	0.3731 in

Torsional Properties:

St. Venant Torsion Constant	$J \times 1000$	0.3692 in ⁴
Warping Constant	C_w	0.1227 in ⁶
Distance Between Shear Axis and Neutral Axis	x_0	-0.6484 in
Polar Radius of Gyration	r_0	1.6260 in
Torsional Flexural Constant	β	0.8410
Limit of Unbraced Length	L_u	16.81 in



Effective Section Properties:

Effective Area	Aeff	0.2245 in ²
Effective Moment of Inertia for Deflection	Ixe	0.6353 in ⁴
Effective Section Modulus	Sxe	0.3114 in ³
Allowable Bending Moment	Ma	9.3247 in.k
Allowable Shear Force (Solid Section)	Vag	3372 lbs

Codes & Standards:

- Calculations are based on AISI S240-20 and AISI S100-16 (2020) w/S2-20.
- Complies with IBC 2024. ASTM C955. ASTM C754. ASTM A653. ASTM A1003. ASTM E72
- LEED / Sustainability Credits: Environmental Product Declaration S-P Code: S-P-00869